

TECHNICAL SPECIFICATIONS



	Cyrano 1.1 HFT				Cyrano 1.1								Cyrano 1.3								
Code	423157				423158								423159								
Sizes	90WP	100WP	110WP	120WP	42NP	55NP	55WP	70WP	90WP	100WP	110WP	120WP	42NP	55NP	55WP	70WP	90WP	100WP	110WP	120WP	
Hydroformed barrel	■																				
Internal barrel off-axis	■				■								■								
Streamlined profile	■																				
Shaft Race	Ømm	7	7	7	7				7	7	7	7					8	8	8	8	
	cm	97	107	122	132				97	107	122	132					97	107	122	132	
Threaded shaft	Ømm					7	7	7	7					8	8	8	8				
	cm					35,9	56,9	56,9	67,1					36,9	51,9	51,9	66,9				
Operating pressure BAR	22	24	24	26	13	16	16	20	22	24	24	26	13	13	13	16	16	18	18	22	
Internal barrel	11 mm	■				■															
	13 mm													■							
Compact head	■				■								■								
Connecting piston	Ømm 1,5	■				■								■							
	Ømm 3																				
Ergonomic handle	■				■								■								
Grip KJ	■																				
Stainless steel side line releaser	■				■								■								
Stainless steel trigger	■				■								■								
Cone with steel line guide	■				■								■								
Dedicated case included	■				■								■								
Manual injector included	■				■								■								



	Sten 11		Sten							Jet					
Code	425151		413105							413106					
Sizes	58WP	70WP	42NP	58WP	58NP	70WP	70NP	84WP*	100WP*	42NP	58WP	58NP	70WP	70NP	
Hydroformed barrel															
Internal barrel off-axis															
Streamlined profile															
Shaft Race	Ømm														
	cm														
Threaded shaft	Ømm	7	7	8	8	8	8	8	8	8	8	8	8	8	
	cm	35,9	56,9	36,9	51,9	51,9	66,9	66,9	86,9	98,4	36,9	51,9	51,9	66,9	66,9
Operating pressure BAR	16	20	13	13	13	16	16	16	18	13	13	13	16	16	
Internal barrel	11 mm	■													
	13 mm			■							■				
Compact head	■									■					
Connecting piston	Ømm 1,5	■		■							■				
	Ømm 3										■				
Ergonomic handle	■		■							■					
Grip KJ	■														
Side line releaser	■		■							■					
Cone with steel line guide	■		■							■					
Dedicated case included	■														
Manual injector included	■		■							■					

With power adjusting system, never exceed the maximum pressure of 30 BAR / 3000 kPa / 435 PSI.

* Until stock lasts